

FLEXO ANILOX NEUTRAL

Galaxy Flexo Anilox Neutral is a strong cleaning solvent for cleaning anilox rollers with water-based, UV, conventional and hybrid inks.

Application: Suitable for both automatic and manual application. For cleaning anilox rollers with water-based, UV, conventional and hybrid inks.

Flexo Anilox Neutral has very good cleaning properties and is completely water miscible.

Does not react with light metals

Procedure to use: For manual application, moisten a clean cloth with pure Flexo Anilox Neutral or a 50 % mix with water, and clean the anilox rollers. When all ink is removed, make a final rinse with a clean cloth and clean water.

For automatic wash equipment follow the instructions from the machine manufacturer.

Product parameters:	Appearance	Transparent liquid
	Specific gravity	1.00 – 1.03 g/cm ³
	Flash point	> 100 °C
	pH	7.5 – 8.5

Storage conditions: Store at room temperature conditions. Keep away from open fire and heat sources.

Shelf life: In unopened, original packaging, 12 months from manufacturing date

Packaging: 20ltr jerrycan

Version: 01-2012

The information provided in this technical data sheet is to inform our customers. A successful application depends on a variety of different factors. Therefore, the advice given in this technical data sheet cannot be used as basis for claims. Our recommendation is where possible to perform tests before entering production runs. We reserve the rights to change product characteristics because of technical progress, amendment of applicable law and mandatory production related needs.