PrintCare RUBBERBLANKETS

ISO 9001:2008




Converted by AtéCé Graphic Products



www.atece.com

AtéCé Graphic Products Molenwerf 14 - 1911 DB Uitgeest P.O. Box 49 - 1910 AA Uitgeest The Netherlands

T +31 (0) 251 - 319109 F +31 (0) 251 - 315850 E info@atece.com







PrintCare Rubber Blankets

SF-A

PrintCare SF-A is characterized by more microsphere compressible layer, which combines a long blanket life with good print quality. The micro-ground surface guarantees excellent print results in screen as well as in solid print. Ink and paper dust build-up is minimized and thus leading to prolonged wash intervals.

INNOVATION AtéCé a major global blanket converter leads the industry with innovative blanket development. Our commitment is to continue developing and delivering innovative products that improve TECHNOLOGY PrintCare compressible layer is the most advanced production technique available and is the next generation in blanket manufacturing. RELIABILITY The consistency and quality of our new PrintCare compressible layer technology and improved gauge control from our advanced buffing techniques gives a superior result, faster recovery on press, improved smash resistance and reduces gauge loss. VALUE Improvements provided by PrintCare compressible layer means exceptional long life from the blanket, improving production time and reducing down-times on press. ECOLOGY PrintCare compressible layer production is solvent free, another first in innovation from AtéCé. Surface Rubber compound Surface finish Micro-grinded Roughness (Ra) 0,7-0,8 µm Colour Light Blue Comstruction 1.96 mm Fabric plies 4 ply physical property 78 ° Thickness range 1.96 ± 0.02 mm Overall hardness (Shore A) 78 ° Tensibile ityre design Xir or 38 % at 135 N/cm ² Elongation at 10 N/mm < 2%				
the next generation in blanket manufacturing. RELIABILITY The consistency and quality of our new PrintCare compressible layer technology and improved gauge control from our advanced buffing techniques gives a superior result, faster recovery on press, improved smash resistance and reduces gauge loss. VALUE Improvements provided by PrintCare compressible layer means exceptional long life from the blanket, improving production time and reducing down-times on press. ECOLOGY PrintCare compressible layer production is solvent free, another first in innovation from AtéCé. Surface Nicro-grinded Roughness (Ra) 0,7-0,8 µm Colour Light Blue Construction Nicrosphere PrintCare Nominal thickness 1.96 mm Eabric plies 4 ply physical property Thickness (Shore A) Thickness range 1.96 ± 0.02 mm Overall hardness (Shore A) 78 ° Tensile strength at break > 35 N/rmm Compressibility indentation approx 8 % at 135 N/cm ²	INNOVATION	development. O	ur commitment is to continue developing and delivering innovative	
improved gauge control from our advanced buffing techniques gives a superior result, faster recovery on press, improved smash resistance and reduces gauge loss. VALUE Improvements provided by PrintCare compressible layer means exceptional long life from the blanket, improving production time and reducing down-times on press. ECOLOGY PrintCare compressible layer production is solvent free, another first in innovation from AtéCé. Surface Rubber compound Surface finish Micro-grinded Roughness (Ra) 0,7-0,8 µm Colour Light Blue Compressible layer design Microsphere PrintCare Nominal thickness 1.96 mm Fabric plies 4 ply physical property Thickness range 1.96 ± 0.02 mm Overall hardness (Shore A) 78 ° Tensile strength at break > 35 N/mm Compressibility indentation approx 8 % at 135 N/cm²	TECHNOLOGY			
the blanket, improving production time and reducing down-times on press. ECOLOGY PrintCare compressible layer production is solvent free, another first in innovation from AtéCé. Surface Rubber compound Rubber compound For hybrid sheetfed application Surface finish Micro-grinded Roughness (Ra) 0,7-0,8 µm Colour Light Blue Compressible layer design Microsphere PrintCare Nominal thickness 1.96 mm Eabric plies 4 ply Physical property Thickness range Thickness range 1.96 ± 0.02 mm Overall hardness (Shore A) 78 ° Tensile strength at break > 35 N/mm Compressibility indentation approx 8 % at 135 N/cm²	improved gauge		e control from our advanced buffing techniques gives a superior result,	
AtéCé. surface Rubber compound For hybrid sheetfed application Surface finish Micro-grinded Roughness (Ra) 0,7-0,8 µm Colour Light Blue construction Compressible layer design Microsphere PrintCare Nominal thickness Nominal thickness 1.96 mm Fabric plies 4 ply physical property Thickness range Overall hardness (Shore A) 78 ° Tensile strength at break > 35 N/mm Compressibility indentation approx 8 % at 135 N/cm²	VALUE	Improvements provided by PrintCare compressible layer means exceptional long life from the blanket, improving production time and reducing down-times on press.		
Rubber compound For hybrid sheetfed application Surface finish Micro-grinded Roughness (Ra) 0,7-0,8 µm Colour Light Blue Construction Microsphere PrintCare Nominal thickness 1.96 mm Fabric plies 4 ply Physical property 1.96 ± 0.02 mm Overall hardness (Shore A) 78 ° Tensile strength at break > 35 N/mm Compressibility indentation approx 8 % at 135 N/cm²	ECOLOGY			
Surface finish Micro-grinded Roughness (Ra) 0,7-0,8 µm Colour Light Blue construction Compressible layer design Microsphere PrintCare Nominal thickness 1.96 mm Eabric plies 4 ply physical property Thickness range 1.96 ± 0.02 mm Overall hardness (Shore A) 78 ° Tensile strength at break > 35 N/mm Compressibility indentation approx 8 % at 135 N/cm²	surface			
Compressible layer design Microsphere PrintCare Nominal thickness 1.96 mm Eabric plies 4 ply physical property Thickness range 1.96 ± 0.02 mm Overall hardness (Shore A) 78 ° Tensile strength at break > 35 N/mm Compressibility indentation approx 8 % at 135 N/cm²	Surface finish Roughness (Ra)		Micro-grinded 0,7-0,8 μm	
Nominal thickness 1.96 mm Fabric plies 4 ply physical property Thickness range 1.96 ± 0.02 mm Overall hardness (Shore A) 78 ° Tensile strength at break > 35 N/mm Compressibility indentation approx 8 % at 135 N/cm²	constructio	on		
Thickness range1.96 ± 0.02 mmOverall hardness (Shore A)78 °Tensile strength at break> 35 N/mmCompressibility indentationapprox 8 % at 135 N/cm²	Nominal thickness		1.96 mm	
Overall hardness (Shore A)78 °Tensile strength at break> 35 N/mmCompressibility indentationapprox 8 % at 135 N/cm²	physical pi	roperty		
Elongation at 10 N/mm < 2%	Overall hardness (Shore A) Tensile strength at break		78 ° > 35 N/mm	
	Elongation at 10	N/mm	< 2%	

