



## G-CUTTER B1+

LST03II-0912-RM

Graphic automatic digital cutting system



**01/ Multiple working mode**

B1+ Single pass/B2+ Double pass/B3 Triple pass

**02/ Easy job preparation & set up**

No physical dies required.

**03/ CCD camera automatic registration system**

Precise positioning and automatic contour cutting.  
Automatic cutting files management. (\* QR code system)

**04/ Automatic materials feeding system**

Stable & efficient sheet feeding system. (\* Roll to sheet feeding system is optional)

**05/ Compact & versatile cutting head**

Full cutting, kiss cutting, creasing & perforation

**06/ B1+ Ideal one stop solution**

Short-run production, sample making, prototyping designs.



Find us on Wechat

## Applications



Folding cardboard, stickers, graphic designs

## Parameters

G-CUTTER	LST03II-0912-RM
Max. Sheet Size	900*1200mm
Min. Sheet Size	210*297mm
Max. Loading	≤180mm, Max. 40 Kgs
Max. Moving Speed	1500mm/s
Max. Cutting Speed	1200mm/s
Max. Cutting Thickness	≤10mm
Repeat Precision	±0.1mm
Standard	Basler CCD camera, Plotting pen, Laser locating pointer, Passive cutting tool, Active cutting tool, Electric oscillating tool, Creasing wheel tool,
Optional	Dual V-Cut tool / Press cutting tool / Roll to sheet device / JWPS packaging software
Individual vacuum zones	4
Safe device	Infrared sensor, mechanical collision-prevention device(* Optional)
Controller	M5
Transmission system	Synchronous belt
Control system	Servo driver (4 sets)
Interface	Ethernet port
Software	JWCS, QR code system included
File format	DXF、PLT、PDF、HPGL、XML、CF2、AAMA、NC、EPS
Rated power	6.5 Kw
Power supply	Single phase 220V±10%, 50/60Hz
Noise range	75-90 dB
Operating environment	10-35°C, 10-80% humidity
Machine dimension	2598x1901x1148mm 3423x1901x1148mm (Includes collecting bag)
Machine weight	700 KGS

JWEI reserves the rights of final explanation, no further information for any exchanging.

Compatible with:



Officially support by:



Included:



Air compressor

Vacuum pump